

IN THE CLAIMS:

Amendments to the Claims

Please amend the claims as shown below.

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A manufacturing method for a gas discharge type display panel in which a couple of substrates are arranged to be facing to each other, a surrounding area of said ~~substrate~~ couple of substrates is sealed by a sealing glass, and an inside space is used as a discharge space by sealing a discharge gas in an internal space, wherein

by exhausting said inside space when sealing, a said sealing glass is made broken down and a clearance gap between said substrates is controlled to be as desired.

2. (original) A manufacturing method for a gas discharge type display panel in Claim 1, wherein

an amorphous glass or an amorphous glass including a filler are used for sealing a substrate.

3. (original) A manufacturing method for a gas discharge type display panel in Claim 1, wherein

a supply and exhaust pipe is formed on an outside surface of said substrate by using a glass material having a heat resistance higher than said substrate sealing glass.

4. (currently amended) A manufacturing method for a gas discharge type display panel in which a couple of substrates are arranged to be facing to each other, a surrounding area of said ~~substrate couple of substrates~~ is sealed by a ~~a~~ an amorphous sealing glass, and an inside space is used as a discharge space by sealing a discharge gas in an internal space, wherein

a gas unnecessary for ~~an a~~ discharge operation is exhausted from said inside space ~~if a state of~~ under a condition that said amorphous sealing glass is located in a temperature range exceeding its softening point and no more than its working point.

5. (currently amended) A manufacturing method for a gas discharge type display panel in which a couple of substrates are arranged to be facing to each other, a surrounding area of said ~~substrate couple of substrates~~ is sealed by a ~~sealing glass~~ glasses, and an inside space is used as a discharge space by sealing a discharge gas in an internal space, wherein

said surrounding area of said couple of substrates are is sealed at least doubly by said sealing glasses each having an individual softening point different from each other, one of said sealing glasses having one individual softening point sealing said surrounding area, and another of said sealing glasses having another individual softening point and disposed adjacent to and substantially parallel with said one of said sealing glasses so as to individually effect sealing of at least the same said surrounding area.

6. (currently amended) A manufacturing method for a gas discharge type display panel in which a couple of substrates are arranged to be facing to each other, a surrounding area of said ~~substrate couple of substrates~~ is sealed by a sealing glass, and an inside space is used as a discharge space by sealing a discharge gas in an internal space, wherein

a protruding portion having a curvature radius between 0.1 mm and 1mm is formed on an overall periphery of said sealing glass at its inside space.

7. (currently amended) A manufacturing method for a gas discharge type display panel in which a couple of substrates are arranged to be facing to each other, a surrounding area of said ~~substrate~~couple of substrates is sealed by a sealing glass, and an inside space is used as a discharge space by sealing a discharge gas in an internal space, wherein

at least at one portion of a ~~said~~ surrounding area of said ~~substrate~~couple of substrates, a cross-section of said sealing glass viewed vertically to a substrate of said couple of substrates is shaped so as to be convex with respect to an ~~said~~ inside space at both its inside space end part and its outside end part.

8. (currently amended) A manufacturing method for a gas discharge type display panel in which a couple of substrates are arranged to be facing to each other, a surrounding area of said ~~substrate~~couple of substrates is sealed by a sealing glass, and an inside space is used as a discharge space by sealing a discharge gas in an internal space, wherein

at least at one portion of a ~~said~~ surrounding area of said ~~substrate~~couple of substrates, a concentration of filler at an inside space end part of said sealing glass is larger than that in other portions.

9. (currently amended) A manufacturing method for a gas discharge type display panel in which a couple of substrates are arranged to be facing to each other, a surrounding area of said ~~substrate~~couple of substrates is sealed by a sealing glass, and an inside space is used as a discharge space by sealing a discharge gas in an internal space, wherein

a glass layer having a heat resistance higher than said sealing glass is formed over an entire periphery of said inside space so as to be adjacent to an inside space end part of said sealing glass or within 2 mm from ~~an~~ the inside space end part.

10. (previously presented) A manufacturing method according to claim 7, wherein a gas unnecessary for a discharge operation is exhausted from said inside space if a state of said sealing glass is located in a temperature range exceeding its softening point and no more than its working point.

11. (previously presented) A manufacturing method according to claim 7, wherein at least at one portion of a surrounding area of said substrate, a concentration filler at an inside space end part of said sealing glass is larger than that in other portions.

12. (previously presented) A manufacturing method according to claim 7, wherein a glass layer having a heat resistance higher than said sealing glass is formed so as to be adjacent to an inside space and part of said sealing glass or within 2 mm from an end part.

13. (currently amended) A manufacturing method according to claim 7, wherein another sealing glass is provided so that said couple of substrates are sealed at least doubly by said sealing glass and ~~said~~ another sealing glass, each having an individual softening point different from each other.

14. (previously presented) A manufacturing method according to claim 7, wherein by exhausting said inside space when sealing, said sealing glass is made broken down and a clearance gap between said substrates is controlled to be as desired.